



News for 01/09/09

Four New Carbs

Hi again,

The addition of two new sizes to the **dAM** Billet 4150 series and two more to the **dAM** Ultimate 4150 series means better optimization to your needs.

The 1.515" venturi 4150 style carb is suited for engines in the 450-725 HP range.
The 1.585" venturi 4150 style is suited for 450-775 HP engines restricted to a 1-11/16" base plate.

The 1.650" venturi Ultimate 4150 is suited for 500-900 HP range while the 1.700" venturi Ultimate would be for 600-1000 HP.

The continuing expansion of the **dAM** product line has prompted us to put together a comprehensive chart of all our carbs and their major specs - see below. Options and custom primary/secondary combos can further enhance optimization.

John



Style	Venturi	Butterfly	Booster Type	CFM @ 10"	CFM @ 20"	Wet CFM @ 17"	HP Range
4150 2V	1.575	1.750	Skirted	473.5	664.5	400	300-450
4150 2V	1.700	1.875	Bottom / Shear	525	728	476	325-500
4150 2V	1.825	2.000	Bottom / Shear	600	796	532	350-550
4150	1.250	1.688	Down Leg	528	761	600	250-650
4150	1.475	1.688	Skirted	650	820	640	350-700
4150	1.515	1.688	Skirted	675	900	680	450-725
4150	1.585	1.688	Skirted	700	933	760	450-775
4150	1.585	1.750	Skirted	720	994	788	500-850
4150	1.585	1.750	Straight	TBA	1050	802	575-900
Ultimate	1.650	1.750	Skirted	TBA	TBA	TBA	500-900
Ultimate	1.700	1.875	Bottom / Shear	TBA	TBA	TBA	600-1000
Ultimate	1.875	2.000	Bottom / Shear	TBA	1358	1022	650-1100
4500	1.575	1.750	Skirted	947	1329	800	600-900
4500	1.700	1.875	Bottom / Shear	1050	1456	952	650-1000
4500	1.825	2.000	Bottom / Shear	1200	1592	1064	700-1100
4500	1.950	2.125	Bottom / Shear	TBA	1682	1292	700-1200
4500	2.090	2.250	Bottom / Shear	TBA	TBA	1420	800-1325
4500	2.090	2.375	Bottom / Shear	TBA	TBA	1510	850-1400
4150 X 2	1.475	1.688	Skirted	1440	1988	1576	600-700
4150 X 2	1.515	1.688	Skirted	TBA	2100	1604	650-725
4150 X 2	1.585	1.688	Skirted	TBA	TBA	TBA	650-775
4150 X 2	1.585	1.750	Skirted	TBA	TBA	TBA	700-850
4150 X 2	1.585	1.750	Straight	TBA	2716	2044	775-900
Splits	1.575	1.750	Skirted	1894	2658	1600	850-1100
Splits	1.700	1.875	Bottom / Shear	2100	2912	1904	775-1150
Splits	1.825	2.000	Bottom / Shear	2400	3184	2128	800-1200
Splits	1.950	2.125	Bottom / Shear	TBA	3364	2584	900-1400
Splits	2.090	2.250	Bottom / Shear	TBA	TBA	2840	950-1500
Splits	2.090	2.375	Bottom / Shear	TBA	TBA	3020	1000-1800
4500 X 2	1.575	1.750	Skirted	1894	2658	1600	750-1100
4500 X 2	1.700	1.875	Bottom / Shear	2100	2912	1904	775-1150
4500 X 2	1.825	2.000	Bottom / Shear	2400	3184	2128	800-1200
4500 X 2	1.950	2.125	Bottom / Shear	TBA	3364	2584	900-1400
4500 X 2	2.090	2.250	Bottom / Shear	TBA	TBA	2840	950-1500
4500 X 2	2.090	2.375	Bottom / Shear	TBA	TBA	3020	1000-1800

PS: \$200. reward for a copy of my cam & valve timing event presentation at Superflow on VHS, please contact me.

If you do not wish to receive this News Letter, just reply with REMOVE.
Please quote or forward the complete News Letter to help us remove the correct address.